

VOYAGER 7050 DMi



stage **5V**

Control panel




Variable speed Kubota engine



Fuel inlet and outlet



Unit of measure: mm



We reserve the right to change data, images and drawings without notice.
For more information, you may contact your local dealer or Mase Generators S.p.A.

Mase Generators spa
Via Tortona, 345 - 47522 - Cesena (FC) - Tel. +39 0547 354311
www.masegenerators.com - commercial@masegenerators.com

mase
GENERATORS
Believing in change.

Description

- Vehicular power generator
- Super silenced version
- Diesel engine variable speed

Standard Features

- Remote control panel with 10 mt cable
- Built-in control panel
- Start and stop buttons
- Auto engine protection shutdown system
- Engine failure warning lights
- Operation lamp
- Power output protection
- Faults memory
- Hourmeter
- Emergency stop switch
- Built-in muffler

Options

- 20 Lt plastic fuel tank with brackets
- 20 Lt steel fuel tank with brackets
- Low fuel indicator kit
- Fuel filler with key lock cap
- 1 mt tank connection pipe with fuel filler
- 2 Mt remote exhaust flexible pipe
- Input/Output fuel pipe to the tank

Noise level

- Lwa 84 (59 dB a 7 mt)

AC generator - 50Hz

- Type: PMG
- Single-phase power (max.): 8,8 kVA - 230V
- Power Factor: $\cos \phi$ 0,8

Diesel Engine variable speed

- Type: Kubota D602 - 2 cyl. - 14,5 hp (10,8 kWm) - 599 cm³
- Cooling system: liquid
- Starting system: electric
- Fuel consumption @ 75%: 2,2 lt/h

Other features

- Insulation Class: H
- Ambient temperature: 40 °C (*)
- Altitude: 1000 mt (*)
- Mechanical Protection: IP 23
- Dimensions (L x W x H): 908 x 560 x 661 mm
- Dry weight: 210 kg

(*) - For altitude and temperature values other than those listed above, please consult the manufacturer to verify the available power.